

HS-3410A / HS-3414A



Specification	HS-3410A	HS-3414A
Processor	Rockchip RK3568, Quad-core Cortex A55 up to 2.0GHz	
System Memory	DDR4 4GB or 8GB	
Storage Device	32 GB to 128 GB eMMC + microSD slot x 1	
Power Supply	24V/60W	
Built-in Printer	PP-7900, 3" speedy thermal printer, 250 mm/sec (max.)	
Built-in WiFi	N/A	
OS Support	Android 11*	
Display & Touch		
LCD	9.7" TFT LCD	14" TFT LCD
Resolution	1024 x 768	1366 x 768
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)	
I/O & Expansion		
Serial Port	DB9 x 2, 5V/12V support on all COM ports	
Parallel Port	N/A	
Standard USB Port	3, USB 3.0 x 1 + USB 2.0 x 2	
OTG USB	Micro-USB x 1 (OTG and USB 3.0 HOST feature are selected by DIP SW)	
LAN Port	10/100/1000 Mb x 1	
Display Port	HDMI x 1, SDK available for software integration	
CR Port	1, controlling 2 CR (24V drive)	
PS/2 Port	N/A	
Audio	2W speaker x 1 + lineout x 1	
Expansion Slot	Mini-PCIe slot x 1	
Physical Dimension		
Dimension (W x D x H in mm)	244 x 210 x 437	371 x 210 x 476
Weight (N. W. in kg)	4.2	5.8
Environmental		
Operating Condition	0°C - 50°C, 20%RH - 90%RH	
Storage Condition	-20°C - 70°C, 10%RH - 90%RH	
Built-in Options		
WiFi	Mini-PCIe WiFi/ BT module	
MSR	3 tracks ISO or JISII (HID/VCOM selection)	
Fingerprint Sensor	Optical type	
RFID Reader	Support MIFARE Ultralight and Classic 1K card (HID/VCOM Selectable)	
Scanner	2D barcode scanner	
iButton	Yes (cannot coexist with Fingerprint Sensor)	
4G / LTE Communication	Single SIM slot, selected band support	
Attachment Options		
POS Monitor	Non-touch TFT LCD: 9.7"/10.1"; PCAP touch TFT LCD: 9.7"/10.1"	
Line Display	2 x 20 rear-mount VFD customer line display; 2 x 20 rear-mount LCD customer line display	

*Google Play services is not supported by this device.

*Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

*The product information and specifications are subject to change without prior notice.

*Please refer to the website for more attachment options.



Precision-Engineered Versatility

HS-3410A / HS-3414A

Most Affordable All-In-One POS Solution



Certifications: EN20230905V2



POSIFLEX TECHNOLOGY, INC.

No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan
 Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw
 Fax : +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller