

Your Versatile Partner



TX-1000AE



TX-1000A

TX-1000A/1000AE

Multi-Purpose Control Box

TX-1000A/1000AE

Specification	TX-1000A	TX-1000AE
Processor	Rockchip RK3399, Dual-core Cortex A72 up to 1.8GHz + Quad-core Cortex A53 up to 1.4GHz	
System Memory	DDR4 4GB	
Storage Device	32GB eMMC + microSD	
RAID Function	N/A	
Intel vPro Support	N/A	
TPM	N/A	
Power Supply	12V/40W	12V/150W
OS support	Android 10 with GMS	

I/O & Expansion

Serial Port	2 x DB9 + 1 x RJ45 + COM5/6 via optional converter cable from service window (5V/ 12V support on all COM ports)	
Parallel Port	N/A	
Standard USB Port	1 x USB 3.0 + 5 x USB 2.0 + 1 x OTG Micro-USB	
PoweredUSB Port	N/A	1 x 24V + 2 x 12V
LAN Port	10/100/1000 Mb x 1	
Display Port	2 x HDMI (HDMI2 support video signal only)	
CR Port	1, control 2 CR via optional Y-cable, 24V support	
PS/2 Port	N/A	
Audio	1 x 2W speaker + 1 x mic-in/line-out	
Expansion Slot	1 x M.2 2230 for Wi-Fi/BT	

Physical Dimension

Dimension (W x D x H in mm)	220 x 202 x 56
Weight (N. W. in kg)	1.2

Environmental

Operating Condition	0°C - 40°C, 20%RH - 90%RH
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

*Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

*The product information and specifications are subject to change without prior notice.

*Please refer to the website for more attachment options.

Certifications	      	EN20240415V1
----------------	--	--------------

POSIFLEX

POSIFLEX TECHNOLOGY, INC.

No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan

Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw

Fax : +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller